

# RETREAD SPECIFICATIONS

The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	ST355	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
295/80R22.5	RH621	660.0	26.0	220.0	8.66	9.00
315/80R22.5		762.0	30.0	240.0	9.45	9.00
11R22.5	TR528	660.0	26.0	210.0	8.27	8.25
11R24.5		660.0	26.0	210.0	8.27	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	210.0	8.27	8.25
215/75R17.5	RH620	559.0	22.0	160.0	6.30	6.00
235/75R17.5		660.0	26.0	180.0	7.09	6.75
225/70R19.5		711.0	28.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
265/70R19.5	RH621	610.0	24.0	200.0	7.87	7.50
285/70R19.5		610.0	24.0	230.0	9.06	8.25
245/70R17.5	RH647	711.0	28.0	200.0	7.87	6.75
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5	610.0	24.0	220.0	8.66	8.25	
295/75R22.5	RH647SP	711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
215/75R17.5		559.0	22.0	175.0	6.89	6.00
225/70R19.5	RH647SP	711.0	28.0	185.0	7.28	6.75
245/70R19.5		711.0	28.0	225.0	8.86	7.50
215/75R17.5	RT785	508.0	20.0	155.0	6.10	6.00
10R22.5	RD796	610.0	24.0	200.0	7.87	7.50
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
11R22.5	DT890	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	CD871	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5		CD883	660.0	26.0	220.0	8.66
11R24.5	660.0		26.0	220.0	8.66	8.25
295/75R22.5	711.0		28.0	220.0	8.66	9.00
285/75R24.5	AP868	711.0	28.0	220.0	8.66	8.25
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
315/80R22.5	RD798	762.0	30.0	230.0	9.06	9.00
11R22.5		711.0	28.0	235.0	9.25	8.25
11R24.5		711.0	28.0	235.0	9.25	8.25
11R22.5	DT990	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
12R22.5		660.0	26.0	240.0	9.45	9.00
315/80R22.5	MS663	838.0	33.0	265.0	10.43	9.00
385/65R22.5	DX770	1067.0	42.0	310.0	12.20	11.75
425/65R22.5		1067.0	42.0	330.0	12.99	12.25
445/65R22.5	DX775	1067.0	42.0	350.0	13.78	13.00
385/65R22.5	DX670	1067.0	42.0	315.0	12.40	11.75
385/55R22.5		991.0	39.0	335.0	13.19	12.25
225/70R19.5	CD883SP	813.0	32.0	190.0	7.48	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
11R22.5	AP866	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
315/80R22.5		762.0	30.0	230.0	9.06	9.00
11R22.5	RH652	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	210.0	8.27	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
445/50R22.5	TR601	2489.0	98.0	400.0	15.75	14.00
445/50R22.5	CD901	2489.0	98.0	400.0	15.75	14.00

